

/ 1, 20 APPROVAL te of Callfo		cers or the accuracy	-31-03	NEER
now has a	web site! To get	to the web site, go to: http	≿//www	dof.ca.gov
now has a	web site! To get	to the web site, go to: http	oz//www	dof.ca.gov

POLE DATA			BASE PLATE DATA						
	Min OD					Anchor Bolts		610 mm	Structural Steel plus 3.5%
Height	Base	Тор	Thickness	"C"	Thickness	Size	BC = Bolt Circle	(24") CIDH Pile	Galvanizing
7.62 m (25')	187 mm (73/8")	98 mm 4.55 mm			25.4 mm	25 mm × 920 mm × 102 mm (1" × 36" × 4")	267 mm (101/2")	1.83 m (6')	180 kg (395 lbs)
9.14 m (30')	203 mm (8")						279 mm (II")	2.13 m (7')	215 kg (475 lbs)
10.67 m (35')	219 mm (85%'')						305 mm (12")	2.13 m (7')	250 kg (550 lbs)
12.19 m (40')	238 mm (93/8")							2.13 m (7')	295 kg (650 lbs)
13.72 m (45')	254 mm (10")					(1 ¹ / ₄ " × 36" × 4")	343 mm (131/ ₂ ")	2.44 m (8')	340 kg (750 lbs)
	7.62 m (25') 9.14 m (30') 10.67 m (35') 12.19 m (40')	H Height Base 7.62 m (25') 187 mm (73'g")	Height Bose Top 7.62 m (25') 187 mm (7\%") 9.14 m (30') 203 mm (8") 10.67 m (35') 219 mm (8\%") 12.19 m (40') 238 mm (9\%") 12.19 m (40') 238 mm (9\%")	H Base Top Thickness 7.62 m (25') 187 mm (7¾'') 9.14 m (30') 203 mm (8¾'') 10.67 m (35') 219 mm (8¾'') 12.19 m (40') 238 mm (9¾'') 12.19 m (40') 238 mm (9¾'')	Height Bose Top Thickness "C" 7.62 m (25') 187 mm (7\%") 9.14 m (30') 203 mm (8") 10.67 m (35') 219 mm (8\%") 12.19 m (40') 238 mm (9\%") 12.19 m (40') 328 mm (9\%") 13.76 mm (0.1793") 13.76 mm	Haight Min OD Thickness "C" Thickness Top Thickness Thickness Top Thickness Thickness Top Thickness Thic	Height Base Top Thickness "C" Thickness Size	Height Base Top Thickness "C" Thickness Size BC = Bolt Circle	Height Base Top Thickness "C" Thickness Size BC = Bolt Circle COMP Pile





ELEVATION

0



CAMERA MOUNTING PLATE





GENERAL NOTES:

SPECIFICATIONS

Design: AASHTO specifications for the design and construction of structural supports for highway signs, dated 1994.

LOADING

Wind Loadings: I29 km/h (80 mph) AASHTO

UNIT STRESSES

Structural Steel: fy = 331 MPa (48,000 psi) tapered steel tube (pole) fy = 248 MPa (36,000 psi) unless otherwise noted

Anchor bolts = A307

Reinforced Concrete: fc = 22.4 MPa (3250 psi) fy = 276 MPa (40,000 psi)

- I. The Contractor shall verify all controlling field dimensions before ordering or fabricating any material.
- 2.All steel shall be galvanized after fabrication.
- 3.During pole erection, the post shall be raked as necessary with the use of leveling leveling nuts to provide a plumb pole axis.

STATE OF CALIFORNIA DEPARTMENT OF TRANSPORTATION CLOSED CIRCUIT TELEVISION POLE DETAILS

These "Standard Plans for Construction of Local Streets and Roads" contain units in two systems of measurement: International System of builts (SI or "metric") and United States Standard Measures shown in the parentheses (). The measurements expressed in the two systems are not necessarily equal or interchangeable. See the "Foreword" at the beginning of this publication.

NO SCALE

ES-16A